


GRAPHENE



01-701

SPECIFICATION SHEET



FEATURES

LINER

Grey Kyorene® Liner,
Fine Gauge

COATING

Black MicroFoam Nitrile
Palm Coating

BENEFITS:

ANSI Cut Level A6
ISO 13997 Level F
Excellent Cut Resistance
Excellent Abrasion Resistance
Excellent Heat Resistance
Anti-Bacterial
High Tensile Strength
UV Resistance
Lightweight

CATEGORY:

Kyorene®

APPLICATIONS:

Aerospace
Appliance Manufacturing
Automotive Manufacturing
Construction
Glass Work
Logistics
Packaging
Metal Fabrication
Plastic Injection Molding

SPECIFICATIONS

LINER MATERIALS	Grey Kyorene® Liner
COATING MATERIALS	Black MicroFoam Nitrile
WRIST DESIGN	Continuous Knit
SIZES	6-11

PACKAGING						
CASE SIZE	6	7	8	9	10	11
PER CARTON	72	72	72	72	72	72
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
ORIGIN	PRC					

PERFORMANCE LEVEL

EN388: 4442F	EN Level 4 Cut Resistance					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5
ISO 13997	A	B	C	D	E	F

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface.
Drying temperatures should not exceed 70°C (158°F)

NEW LEVELS

EN388



4442F

ABRASION (1 - 4)

BLADE CUT (1 - 5)

TEAR (1 - 4)

ISO 13997 (A - F)

PUNCTURE (1 - 4)