



# **OIL & GUT RES**

### **PRODUCT**

Style No. 542 Material Nitrile

Liner 13-Gauge | Seamless

HPPE/Glass fiber

Size 7/S-11/XXL

Color Coating: Blue & Black, Liner: Gray

Size & Hem Color

8/M 9/L 10/XL 11/XXL

## **TECHNICAL**







### **TECHNOLOGY**





### **APPLICATIONS**

Automotive / Assembly / Machine Operation Oily Material Handling / Glass Handling / Sheet Metal Handling

NBR MicroFinish Technology: U.S. Pat.No. 8,387,167 / EP Pat.No. 2143551 ZL200880010847.0



# **DESIGN AND PERFORMANCE THAT WORKS**

### **DESCRIPTION**

The highest protection model of the series. Using the HPPE fiber technology, ActivGrip™ Omega Max achieves the high performance level in cut resistance. In addition, ActivGrip™ Omega Max is designed for maximum liquid proof protection, 360°. Combined with the liquid proof palm and MicroFinish® grip technology, ActivGrip™ Omega Max is ideal for the most extreme tasks and where true reliability of the performance is needed.

### **FEATURES**

### **Maximum Performance**

A lightweight 13-gauge seamless HPPE liner and ergonomic design assures maximum comfort without decreasing the dexterity. The engineered design guarantees the maximum performance without fatigue.

### **Maximum Safety**

With using HPPE fiber, ActivGrip™ Omega Max offers the high cut resistant protection. Fingers are double coated to bring ActivGrip™ Omega Max to the highest level of safety without losing performance, durability and dexterity.

### Liquidproof Palm & Back

The double coated palm surface and coated back keep hands clean and prevents any liquids from outside. ActivGrip™ Omega Max combines maximum performance with hygiene for the ultimate protection of the user's hands.

### **Grip Performance**

Towa's original patented MicroFinish® technology offers the best grip in the industry in dry, wet and oily conditions.

### **GLOVE SERIES**





540 ActivGrip™ Omega

541 ActivGrip™ Omega Plus

# **Towa Corporation**

227 Tsubuku Honmachi, 830-0047 Kurume, Fukuoka, Japan Phone:+81-942-32-8863 Fax:+81-942-31-319